




Detail of perforated hole pattern.



Application


Perforated return R&G are used as return or exhaust units that match the appearance of perforated supply diffusers. They are well suited for locations where the occupant can see into the duct, and can be mounted on the wall or in the ceiling.

Standard Features


- Formed steel construction is durable and inexpensive.
- Optional 304 stainless steel construction.
- Perforated material is 51% free area.
- Minimum grille size is 4" x 4".
- Maximum grille size is 48" x 36." Panels can be joined for larger sizes (p. A312).
- Register uses model RXEA opposed blade damper (p. A437).
- Standard finish is electrocoat acrylic baked enamel.
- Standard color is #11 bright white.

Optional Features

- Tamper-proof screws (p. A342).
- Concealed hangers (p. A343).
- UL-listed fusible link (p. A343).
- Unit can be set in T-bar panel (Opt. T) and certain sizes can be sheared (Opt. S) to fit T-bar grids (p. A341).



Model Numbering System




Sq. & Rect. Registers & Grilles

Multi-Panel Construction for the following Registers & Grilles

Steel
 Louvered Return RSLA, RTLA
 Perforated Return RSFA, RTFA

In-Line Construction






Notes:

1. Panels will be made in even inch increments unless specified otherwise.
2. Dimensions shown are listed size dimensions.
3. Max. blade length on louvered face models is nominal 48".
4. Panels are sheared and aligned with joining strips.


Ganged Construction

Notes:

1. Either the vertical or horizontal joint can be sheared down, but not both.
2. Maximum single panel width is 48" listed size.
3. Maximum blade length on louvered face models is listed size 48".
4. Maximum single panel height is 36" listed size.
5. Panels are made in even inch increments unless specified otherwise.
6. Blade alignment is always parallel to center support.
7. The center support can be aligned vertically or horizontally, depending on the blade alignment desired. It is shown here mounted horizontally.
8. Grille dimensions shown are listed size dimensions.



Cross-Sectional View of Center Support with Grilles Attached





Multi-Panel In-Line Construction


Notes:

1. Maximum single panel width and height is 48" nominal size, regardless of blade alignment.
2. Panels are made in even inch increments unless specified otherwise.
3. Front blade alignment is as pictured.
4. Grille dimensions shown are nominal dimensions.
5. Panel flanges are sheared and aligned with joining strips.

- Height: 50-96"
- Width: Up to 48"
- Two Sections
- Any Blade Alignment





- Height: Over 96"
- Width: Up to 48"
- Three or more Sections
- Any Blade Alignment



- Height: Up to 48"
- Width: 50" - 96"
- Two Sections
- Any Blade Alignment


- Height: Up to 48"
- Width: Over 96"
- Three or more Sections
- Any Blade Alignment







Multi-Panel Ganged Construction

Notes:

1. Maximum single panel width and height are 48" nominal size.
2. Panels are made in even inch increments unless specified otherwise.
3. Front blade alignment is always parallel to center support.
4. Either the vertical or horizontal joint can be sheared down, but not both.
5. The center support can be aligned vertically or horizontally, depending on blade alignment desired.
6. Grille dimensions shown are nominal dimensions.



Cross-Sectional View of Center Support




Center Support Mounted flush with wall (Shown aligned horizontally).


All Sections of Butted Grilles or Registers will be made in Listed Sizes as Standard.

STANDARD REGISTERS AND GRILLES

Applies to all models except louvered return air registers and grilles and door partition grilles.
Registers and grilles over 36" x 36" butting two or more grilles together.



GRILLES AND REGISTERS HAVING FOUR SECTIONS AND OVER



NOTES:

Extruded aluminum supporting members with mounting angles, are furnished where required.

Center support may run vertically or horizontally, depending upon combination of grilles used.




Combination of panels will be furnished to fit duct opening with satisfactory clearance.

Screw Hole Location for the following Registers & Grilles

| | Steel | Aluminum | Stainless Steel |
|-------------------|------------|------------|-----------------|
| Single Deflection | RSSB, RTSB | RASM, RNSM | RLSB, RKSB |
| Double Deflection | RSDB, RTDB | RADM, RNDM | RLDB, RKDB |
| 0° Fixed Return | RSRB, RTRB | RARM, RNRM | RLRB, RKRB |
| 45° Fixed Return | RSAB, RTAB | RAAM, RNAM | RLAB, RKAB |
| Louvered Return | RSLA, RTLA | ----- | ----- |
| Perforated Return | RSFA, RTFA | RAFM, RNFM | ----- |

Notes:

- Screw holes on the face are standard on Registers and Grilles.
- Steel R&G can be ordered without screw holes, for use with concealed hangers (Opt. N).
- The screw holes is 5/32" in diameter.
- Each Register or Grille is provided with the appropriate number of screws as standard.
- The standard screw is #8 x 1-1/4" pan head screw, with a flat blade head.
- Tamper-proof screws are available as an option (Opt. B).



Sq. & Rect. Registers & Grilles