



**DIMENSIONS LISTED IN INCHES**

Model	Wheel	1	2	3	A	C	D	E	F	N	D1	M	D2	H (Max)	Weight (lb)
12	15.75	18	19	21	24	23	22	19	16	8	0	4	1	39	130
15	17.75	20	22	23	28	27	25	21	18	12	0	4	1	42	157
16	19.75	22	24	25	29	28	26	23	19	12	0	4	1	46	201

**DIMENSIONS LISTED IN MILLIMETERS**

Model	Wheel	1	2	3	A	C	D	E	F	N	D1	M	D2	H (Max)	Weight (Kg)
12	400	450	490	530	610	594	550	486	406	8	12	4	15	980	59
15	450	510	550	590	707	691	647	546	456	12	12	4	15	1070	71
16	500	560	610	640	730	714	670	572	482	12	12	4	15	1160	91

**VMBL Standard Features:**

- Fans are tested in an AMCA approved laboratory for air and sound performance.
- Fan casing is constructed out of 14 gauge steel.
- Casing joints are continuously welded.
- Fan design is integrated with casing design to maximize air-straightening effect.
- Impeller is constructed of fabricated steel of all welded construction.
- Polished CRS fan shaft with rust inhibitive coating.
- Bearings are lubricated via extended lubrication lines.
- The V-belt drive consists of cast iron sheaves and anti-static conducting belts.